


CANIS



CANIS

SYSTEM


CANIS system is dedicated for cargo screening in different localizations, including seaports and land borders. It can be achieved thanks to high quality visualization by megavoltage X-ray beam.

TECHNOLOGY

CANIS consists of interlaced energy electron linac 4MeV/6MeV and detector line. Electron beam hits the conversion target and high energy X-rays production occurs. Crated photons are attenuated by the examined goods and detected in the detector line located behind the truck or container. Signals from all detectors are converted to digital form and transferred to operator's PC, where the final image is created, line by line. Dual energy mode allows for Z-related coloring to achieve the highest efficiency of contraband detection.

KEY ADVANTAGES

- High penetration
- Complete object scan at seaports and land borders
- · High safety level
- Efficient inspection of trucks and cargo containers
- Patented interlaced-energy technology
- Perfect image quality
- Dual-energy material discrimination
- Intuitive and highly configurable software, equipped with advanced image processing for ultimate operator's satisfaction
- · Easy setup
- · High reliability
- Low operation cost



Head of CANIS demonstrator team

Eng. Sławomir Wronka, PhD
Particle Acceleration Physics & Technology Division (TJ1)
phone +48 22 71 80 539
slawomir.wronka@ncbj.gov.pl

Head of CANIS team - detectors subgroup

Eng. Arkadiusz Chłopik, MSc Electronics and Detection Systems Division (TJ4) phone +48 22 71 80 550 arkadiusz.chlopik@ncbj.gov.pl



National Centre for Nuclear Research ul. Andrzeja Sołtana 7 PL-05-400 Otwock-Świerk, Poland



AiD project http://www.ncbj.gov.pl/aid aid@ncbj.gov.pl phone +48 22 71 80 465

SWAN has been developed within the project "Development of dedicated systems based on accelerators and detectors of ionizing radiation for medical therapy and in detection of hazardous materials and toxic wastes" supported by EU Structural Funds Project no POIG. 01.01.02-14-012/08-00





